

└10¾"─

⊢8½"⊣

| AVAILABLE FINISHES: | |
|---------------------|--|
| Catalog Number: | |
| Fixture Type: | |
| Location: | |

Project:

Imperial

PD-32242

PRODUCT DESCRIPTION

An architecturally scaled, two tiered pendant offering both pward and downward illumination from energy efficient LEDs. Clean curvaceous lines from the streamlined $\,$ silhouettecomplement the best in today's upscale interiors.

FEATURES

- Driver concealed within the canopy
- Up and down illumination
- Streamlined architectural silhouette
- Spin-on round canopy with minimal hardware
- Thin power aircraft cables provide an ultra clean look for adjustable suspension height

SPECIFICATIONS

| Rated Life | 54000 Hours |
|--------------|--|
| Standards | ETL, cETL,Damp Location Listed |
| Input | 120-277V,50/60Hz |
| Dimming | ELV, 0-10V, TRIAC |
| Color Temp | 3000K |
| CRI | 90 |
| Construction | Bended extruded aluminum body with silicone diffuser |

| Model & Size | Color Temp | Finish | LED Watts | LED Lumens | Delivered Lumens |
|--------------|------------|---|-----------|------------|-------------------------|
| PD-32242 42" | 3000K | BK Black BN Brushed Nickel | 81.8W | 7965 | 3911 |

PD-32242

MIN 29" MAX 120"

331/2"

Example: PD-32242-BN

For custom requests please contact customs@modernforms.com