
# MODERN FORMS MARTFAN





#### PRODUCT DESCRIPTION

From bedrooms to boardrooms, pool houses to patios, Vox works its magic with a compact design that looks great anywhere- even outside. We make all our smart fans wet-rated- that means highly durable materials and weather-resistant finishes- so you can keep a consistent look and feel throughout your décor. Control your smart fan with the exclusive Modern Forms app, which integrates easily with smart devices you already own- if you want to turn it on, all you have to do is ask.

#### **SPECIFICATIONS**

Construction: Aluminum Blade: 13° Pitch, 26" sweep, ABS Downrod: 1" O.D. x 6"H included Mounting Slope: Up to 32°

Lead Wire: 80"

Hanging Weight: 16.50 lbs

Total Power: 41W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20

## **FEATURES**

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Luminaire cover not available
- Includes BT remote control F-RCBT-WT
- Additional remote control with wall cradle sold separately
- Optional wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

## LIGHT KIT PERFORMANCE

**Light Source: LED** Light Wattage: 23.5W **Dimming:** Integrated

Color Temperature: 3000K (2700K / 3500K options available)

Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 Compliant

# **ESTIMATED AIR PERFORMANCE**

Airflow: 2715 cubic ft per minute on high

Power: 17.4 watts on high

Airflow Efficiency: 156 cubic ft per minute per watt Revolutions Per Minute: 269 RPMs on high Estimated Yearly Energy Cost (\$): \$4.00

## **WIRELESS PERFORMANCE**

Bluetooth Range: Up to 150 ft\* Wi-Fi Range: Up to 150 ft\*

### **ORDER NUMBER**

Model	LED Lumens	Delivered Lumens		Housing	Blade
			BZ	Bronze	Bronze
FR-W1802-26L	2041	949	MW	Matte White	Matte White
			МВ	Matte Black	Matte Black

Example: FR-W1802-26L-BZ

For 2700K add "-27"; 3500K add "-35" before the finish: FR-W1802-26L-27-MW

\*Results may vary based on application and surroundings.













modernforms.com Phone (866) 810.6615 (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760



FR-W1802-26L



OPTIONAL ACCESSORIES							
BT Wall Control	F-WCBT		White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.			
BT Remote Control			White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.			
Wi-Fi Touch Panel Wall Control	F-TS	BK WT	Black White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.			
Downrod Couplers	XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in  XF-I	AS BA BZ CFI DW GB GH GW KO	Automotive Silver Brushed Aluminum Bronze Carbon Fiber** Dark Walnut Gloss Black Graphite Gloss White Koa†	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.  Connects two downrods together.			
Sloped Ceiling Kit	XF-SCK	MB MW OB SS TT	Matte Black Matte White Oil Rubbed Bronze Stainless Steel Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.			

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW** 

### SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13'	12′	11'	10′	9′
Downrod	72"	60"	48"	36"	24"	18"	12"

#### SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

\*Koa downrods available in 12", 18", 24" and 36"

modernforms.comHeadquarters/Eastern Distribution CenterCentral Distribution CenterWestern Distribution CenterPhone (866) 810.661544 Harbor Park Drive1600 Distribution Ct1750 Archibald AvenueFax (800) 526.2585Port Washington, NY 11050Lithia Springs, GA 30122Ontario, CA 91760